

3000 ml and the radius R of curvature of the vertex being 3 to 20 mm promotes achieving a desired self-sustainability of said container.

*13* ~~22.~~ A plastic container according to claim 12, wherein the average thickness of said trunk portion being 0.2 to 0.7 mm promotes achieving a desired crushability characteristic of said container, the ratio (H/L) being 2 to 4 and the radius R of curvature of the vertex being 3 to 20 mm promotes achieving a desired space efficiency characteristic of said container, and the amount of the contents of said plastic container being 800 to 3000 ml and the radius R of curvature of the vertex being 3 to 20 mm promotes achieving a desired self-sustainability of said container.

*14*  
23. A plastic container according to claim ~~13~~, wherein the average thickness of said trunk portion being 0.2 to 0.7 mm promotes achieving a desired crushability characteristic of said container, the ratio (H/L) being 2 to 4 and the radius R of curvature of the vertex being 3 to 20 mm promotes achieving a desired space efficiency characteristic of said container, and the amount of the contents of said plastic container being 800 to 3000 ml and the radius R of curvature of the vertex being 3 to 20 mm promotes achieving a desired self-sustainability of said container.

*22*  
*22*  
24. A plastic container according to claim ~~20~~, wherein the average thickness of said trunk portion being 0.2 to 0.7 mm promotes achieving a desired crushability characteristic of said container, the ratio (H/L) being 2 to 4 and the radius R of curvature

48

A